

PRODUCT-DETAILS

CCL5-11

CCL5-11 Auxiliary Contact Block



General Information

Extended Product Type	CCL5-11
Product ID	1ISBN011421R1008
EAN	3471522199133
Catalog Description	CCL5-11 Auxiliary Contact Block
Long Description	CCL5-11 Auxiliary Contact Block

Ordering

EAN	3471522199133
Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	12 mm
Product Net Height	74 mm
Product Net Depth / Length	60 mm
Product Net Weight	0.05 kg

Container Information

Package Level 1 Units	2 piece
-----------------------	---------

Package Level 1 Width	100 mm
Package Level 1 Height	35 mm
Package Level 1 Depth / Length	105.5 mm
Package Level 1 Gross Weight	0.1 kg
Package Level 1 EAN	3471522199133
Package Level 2 Units	box 240 piece
Package Level 2 Width	300 mm
Package Level 2 Height	308 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	2880 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Additional Information

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40
Maximum Electrical Switching Frequency	1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mechanical Durability	10 million
Minimum Switching Capacity	A9 ... A16 / AE9 ... AE16 / N / NE 17 / 5 VLT4K
Mounting Position	Side
Mounting Type	Side Mounting
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Order Multiple	2 piece
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Product Main Type	Accessories for Block Contactors
Product Name	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Frequency (f)	Supply Circuit 50 60 Hz
Rated Insulation Voltage (Ui)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Making Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Operational Current AC-15 (Ie)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (Ie)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A (125 V) 0.55 / 69 A (250 V) 0.3 / 75 A
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 24 V
Remarks	100
RoHS Date	20171115

Suitable For	A9 A12 A16 N22E N31E N40E
--------------	--

Terminal Type	Screw Terminals
---------------	-----------------

Certificates and Declarations (Document Number)

CSA Certificate	CSA_1033838
Data Sheet, Technical Information	1SBC100122C0202_Ch04
Declaration of Conformity - CE	1SBD250809U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250198E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407744P0001
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250809U1000
UL Certificate	UL_071301E48139

Classifications

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
Object Classification Code	K
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

