

PRODUCT-DETAILS

OTR16BA3M

OTR16BA3M Enclosed Switch Disconnecter



General Information

Extended Product Type	OTR16BA3M
Product ID	1SCA022569R5110
EAN	6417019183695
Catalog Description	OTR16BA3M Enclosed Switch Disconnecter
Long Description	The enclosure of the OTR series is made of rigid stainless steel, class AISI304. The enclosure has a hinged door, with door lock. The cover is interlocked, and can not be opened when switch is on. The interlock function can be defeated for thermographing. Suitable for outdoor and indoor use. The cable entries are of knock out types. N- and PE terminal included.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363010
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340006M0013
Mechanical Drawings	OTRK201510S25.stp

Dimensions

Product Net Width	150 mm
Product Net Height	200 mm
Product Net Depth / Length	100 mm
Product Net Weight	1.6 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 16 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 16 A (690 V) 16 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 16 A (690 V) 10 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 0.705 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 0.5 kA
Power Loss	at Rated Operating Conditions per Pole 0.3 W
Pollution Degree	3
Handle Color	Red / Yellow
Handle Type	Selector handle
Position of Line Terminals	Top In - Bottom Out
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Screw Clamp 0.75...10 mm ² Screw Clamp / PE Terminal 2pcs, 1.5...25 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xø25.5+ø16.5 / 2xø25.5+ø16.5
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Stainless steel
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC340006D2704
--------------------------------	-----------------

Instructions and Manuals	1SCC340006M0013
RoHS Information	1SCC340034D0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	162 mm
Package Level 1 Depth / Length	222 mm
Package Level 1 Height	148 mm
Package Level 1 Gross Weight	1.7 kg
Package Level 1 EAN	6417019183695

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

