

PRODUCT-DETAILS

OS400B22N2

OS400B22N2 SWITCH FUSE



General Information

| | |
|-----------------------|---|
| Extended Product Type | OS400B22N2 |
| Product ID | 1SCA022754R9210 |
| EAN | 6417019245997 |
| Catalog Description | OS400B22N2 SWITCH FUSE |
| Long Description | Switch Fuses,Front Operated,4-pole,22 (Between the Poles),British Standard,B1-B4,Handle and shaft not included,Switched - With Solid Link |

Ordering

| | |
|-----------------------|--------------|
| Customs Tariff Number | 85365080 |
| Country of Origin | Finland (FI) |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC311100D0203 |
| Instructions and Manuals | 1SCC311015M0215 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 230 mm |
| Product Net Height | 318 mm |

| | |
|----------------------------|---------------------|
| Product Net Depth / Length | 176 mm |
| Product Net Weight | 7.99 kg 17.61 lb |

Technical

| | |
|--|--|
| Rated Operational Current AC-21A (I_e) | (500 V) 400 A (690 V) 400 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A |
| Rated Operational Power AC-23A (P_e) | (220 ... 240 V) 132 kW (400 V) 220 kW (415 V) 230 kW (500 V) 280 kW (690 V) 400 kW |
| Conventional Free-air Thermal Current (I_{th}) | q = 40 °C 400 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 400 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Voltage | 500 V |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 14 kiloampere rms |
| Rated Conditional Short-Circuit Current (I_{nc}) | (690 V) 80 kA |
| Power Loss | at Rated Operating Conditions per Pole 45 W |
| Pollution Degree | 3 |
| Handle Type | Handle and shaft not included |
| Fourth Pole Position | Right Side |
| Fourth Pole Type | Switched - With Solid Link |
| Switches Operating Mechanism | 22 (Between the Poles) |
| Position of Line Terminals | Top In - Bottom Out, Bottom In - Top Out |
| Fuse Size | B1-B4 |
| Fuse System | British Standard |
| Operating Mode | Front Operated |
| Standards | IEC 60947-3 |
| Mounting Type | Base mounting |
| Number of Poles | 4 |
| Terminal Type | Lug terminals |
| Terminal Width | 25 mm |
| Tightening Torque | 30 ... 44 N·m |
| Fuse Type | BS |

Environmental

| | |
|-------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|--|
| CCC Certificate | CCC OS315-400 2016 |
| Declaration of Conformity - CE | 1SCC311099D2704 |
| DNV GL Certificate | 1SCC311131D0202 |
| EAC Certificate | EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_ pd f |
| Instructions and Manuals | 1SCC311015M0215 |
| RoHS Information | 1SCC311099D2704 |

Container Information

| | |
|--------------------------------|--------------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 240 mm 9.45 in |
| Package Level 1 Depth / Length | 335 mm 13.19 in |
| Package Level 1 Height | 206 mm 8.11 in |
| Package Level 1 Gross Weight | 8.39 kg 18.5 lb |
| Package Level 1 EAN | 6417019245997 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 4 | EC001040 - Fuse switch disconnecter |
| ETIM 5 | EC001040 - Fuse switch disconnecter |
| ETIM 6 | EC001040 - Fuse switch disconnecter |
| ETIM 7 | EC001040 - Fuse switch disconnecter |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

