

PRODUCT-DETAILS

# OT250E10P

## OT250E10P SWITCH-DISCONNECTOR



### General Information

Extended Product Type	OT250E10P
Product ID	1SCA022760R0500
EAN	6417019247700
Catalog Description	OT250E10P SWITCH-DISCONNECTOR
Long Description	1-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301031M0220

## Dimensions

Product Net Width	75.5 mm
Product Net Height	150 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	0.8 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A (1000 V) 250 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 75 kW (400 ... 415 V) 145 kW (500 V) 170 kW (690 V) 250 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 250 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 30 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 8 kA
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 10 (Right Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	1
Degree of Protection	Front IP00
Terminal Type	Lug terminals

Tightening Torque	acc. IEC 60947-1 15...22 N·m
Mechanical Durability	20000
Lock Type	Yes

---

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

---

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301131D2705
DNV GL Certificate	1SCC301174D0204
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301031M0220
RoHS Information	1SCC301149D0203

---

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	160 mm
Package Level 1 Depth / Length	172 mm
Package Level 1 Height	96 mm
Package Level 1 Gross Weight	0.92 kg
Package Level 1 EAN	6417019247700

---

## Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

