

PRODUCT-DETAILS

OT200U04CP

OT200U04CP CHANGE-OVER SWITCH



General Information

Extended Product Type	OT200U04CP
Product ID	1SCA022771R6210
EAN	6417019251806
Catalog Description	OT200U04CP CHANGE-OVER SWITCH
Long Description	The change-over switches include a black handle IP65

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC303008M0201

Dimensions

Product Net Width	237 mm
Product Net Height	150 mm

Product Net Depth / Length	160 mm
Product Net Weight	4.18 kg 9.22 lb

Technical

Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-31B (I _e)	(380 ... 415 V) 250 A
Rated Operational Current AC-33B (I _e)	(380 ... 415 V) 250 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 250 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 8 kiloampere rms
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Mechanical Durability	8000 cycle
Transition Type	Open

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 240 V) 75 Hp (acc. to UL 480 V) 150 Hp (acc. to UL 600 V) 200 Hp
Ampere Rating UL/CSA	200 A

Environmental

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303006D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0201
RoHS Information	1SCC301149D0202

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	186 mm 7.32 in
Package Level 1 Depth / Length	300 mm 11.81 in
Package Level 1 Height	185 mm 7.28 in
Package Level 1 Gross Weight	4.45 kg 9.81 lb
Package Level 1 EAN	6417019251806

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

