

PRODUCT-DETAILS

# OTM800E4CM110V

## OTM800E4CM110V MOTORIZED C/O SWITCH



### General Information

Extended Product Type	OTM800E4CM110V
Product ID	1SCA022872R8260
EAN	6417019339337
Catalog Description	OTM800E4CM110V MOTORIZED C/O SWITCH
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

### Dimensions

Product Net Width	476 mm
-------------------	--------

Product Net Height	250 mm
Product Net Depth / Length	299 mm
Product Net Weight	25 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 720 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 650 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 450 kW (500 V) 560 kW (690 V) 800 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 800 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 800 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 20 kiloampere rms
Motor Operational Voltage	110 ... 125 V AC/DC
Power Loss	40 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Transition Type	Open

## Environmental

Environmental Information	1SCC303036D0202
---------------------------	-----------------

---

## Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	1SCC303033D0201
Environmental Information	1SCC303036D0202
Instructions and Manuals	1SCC303002M0204
RoHS Information	1SCC303036D0202

---



---

## Container Information

---

Package Level 1 Units	1 piece
Package Level 1 Width	310 mm
Package Level 1 Depth / Length	560 mm
Package Level 1 Height	330 mm
Package Level 1 Gross Weight	25.19 kg
Package Level 1 EAN	6417019339337

---



---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641769

---



---

## Categories

---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized Change-over Switches

