

PRODUCT-DETAILS

# OT800E03YP

## OT800E03YP BY-PASS SWITCH



### General Information

Extended Product Type	OT800E03YP
Product ID	1SCA123591R1001
EAN	6417019543758
Catalog Description	OT800E03YP BY-PASS SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

## Dimensions

Product Net Width	315 mm
Product Net Height	250 mm
Product Net Depth / Length	432 mm
Product Net Weight	43.9 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 450 kW (500 V) 560 kW (690 V) 800 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 800 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 800 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 20 kiloampere rms
Power Loss	40 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301196D0202
Instructions and Manuals	1SCC301080M0003

## Container Information

Package Level 1 Units	1 piece
-----------------------	---------

Package Level 1 Width	420 mm
Package Level 1 Depth / Length	680 mm
Package Level 1 Height	440 mm
Package Level 1 Gross Weight	43.9 kg
Package Level 1 EAN	6417019543758

---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual bypass switches

