

PRODUCT-DETAILS

OTDC200U11

OTDC200U11 PV Disconnect Switch



General Information

Extended Product Type	OTDC200U11
Product ID	1SCA123767R1001
EAN	6417019545295
Catalog Description	OTDC200U11 PV Disconnect Switch
Long Description	OTDC200U11 PV Disconnect Switch, Terminal bolt kit included, Handle and shaft need to be ordered separately, Base mounting, UL 1000 VDC 200 A, IEC 1000 VDC 250 A

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Last Ordering Date	2021-11-30 All Countries
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301081M0206
Mechanical Drawings	OTDC100_245U11.igs 1SCC307007F0002

1SCC307008F0002

Dimensions

Product Frame Size	S
Product Net Width	115.5 mm 4.5 in
Product Net Height	176 mm 6.9 in
Product Net Depth / Length	83.5 mm 3.3 in
Product Net Weight	1.2 kg 2.7 lb

Technical

Connection Configuration	Single circuit 2a, 2b
Rated Operational Current DC-21B (I_{θ})	(1000 V) 250 A
Conventional Free-air Thermal Current (I_{th})	250 A
Conventional Thermal Current (I_{the})	Fully Enclosed 250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1500 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V DC) 10 kA
Rated Short-time Withstand Current (I_{cw})	(1000 V DC) 10 kA for 1 s 5 kA for 0.1 s 10 kA
Protection Type	Circuit breaker
Power Loss	at Rated Operating Conditions per Pole 9.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Shaft Diameter	6 mm 0.24 in
Switches Operating Mechanism	Mechanism Between the Poles 11 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	UL98B and IEC 60947-1, -3
Special Functions	No
Mounting Type	Base mounting
Number of Circuits	1
Number of Poles	2
Degree of Protection	Front IP20
Terminal Type	Lug terminals

Terminal Width	19.5 mm 0.77 in
Tightening Torque	Cable Lug 15...22 N·m
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B)

Technical UL/CSA

Maximum Operating Voltage UL/CSA	1000 V DC
Ampere Rating UL/CSA	1000VDC 200 A
Tightening Torque UL/CSA	Cable Lug 10...12 N·m Cable Lug 133...195 lbf·in

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	NA

Certificates and Declarations (Document Number)

CCC Certificate	CQC2013010302611671
CSA Certificate	CSA Letter_of_Attestation OTDC100-200.pdf
Declaration of Conformity - CE	1SCC301201D2703
DNV GL Certificate	1SCC301231D0201
Environmental Information	NA
Instructions and Manuals	1SCC301081M0206
RoHS Information	1SCC301201D2703
UL Certificate	UL certificate OTDC100-200.pdf

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	96 mm 3.8 in
Package Level 1 Depth / Length	160 mm 6.3 in
Package Level 1 Height	244 mm 9.6 in
Package Level 1 Gross Weight	1.4 kg 3 lb
Package Level 1 EAN	6417019545295

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter

ETIM 7

EC000216 - Switch disconnecter

UNSPSC

39122233

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

