

TS 15X5/LL 1M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

Building installation wiring

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Rail, TS 15, with slot, Steel, galvanic zinc plated and passivated
Order No.	0117510000
Type	TS 15X5/LL 1M/ST/ZN
GTIN (EAN)	4008190111298
Qty.	1 m

TS 15X5/LL 1M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	5.5 mm	Depth (inches)	0.217 inch
Height	15 mm	Height (inches)	0.591 inch
Net weight	137.5 g	Width	1,000 mm
Width (inches)	39.37 inch		

Mounting rail

Drill-hole diameter	4.2 mm	
Installation advice	Direct mounting	
Length of the terminal rail	min.	0 mm
	max.	1,000 mm
	nominal	1,000 mm
Material	Steel	
Pre-punched mounting rail	Yes	
Short circuit strength corresponds to E-Cu wire	10 mm²	
Short-time withstand current according to IEC 60947-7-2	1.2 kA/1s	
Slit gap	8 mm	
Slit gap		
Slit length	12 mm	
Slit length		
Slit width	4.2 mm	
Slit width		
Slotted drill holes	Yes	
Solder eyelet hole diameter (D)	4.2 mm	
Spacing of holes, centre-to-centre	20 mm	
Standards	DIN EN 60715	
Surface finish	galvanic zinc plated and passivated	
Thickness	1 mm	

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ECLASS 9.0	27-40-06-02	ECLASS 9.1	27-40-06-02
ECLASS 10.0	27-40-06-02	ECLASS 11.0	27-40-06-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks