

**EWK 1****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                             |
|------------|-----------------------------|
| Version    | Accessories, End bracket    |
| Order No.  | <a href="#">0206 160000</a> |
| Type       | EWK 1                       |
| GTIN (EAN) | 4008 190080020              |
| Qty.       | 50 pc(s).                   |

## EWK 1

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 31 mm      | Depth (inches)  | 1.22 inch  |
| Height         | 27 mm      | Height (inches) | 1.063 inch |
| Net weight     | 4.34 g     | Width           | 9 mm       |
| Width (inches) | 0.354 inch |                 |            |

## Temperatures

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |
|----------------------------------|--------|----------------------------------|--------|

## Material data

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | Wemid | Colour | beige |
| UL 94 flammability rating | V-0   |        |       |

## System specifications

|         |                   |      |       |
|---------|-------------------|------|-------|
| Version | For the terminals | Rail | TS 32 |
|---------|-------------------|------|-------|

## Additional technical data

|                     |                 |           |                  |
|---------------------|-----------------|-----------|------------------|
| Installation advice | Direct mounting | Interlock | for screw fixing |
| Type of mounting    | when screwed in |           |                  |

## Dimensions

|              |         |
|--------------|---------|
| TS 32 offset | 13.5 mm |
|--------------|---------|

## General

|                     |                 |      |       |
|---------------------|-----------------|------|-------|
| Installation advice | Direct mounting | Rail | TS 32 |
|---------------------|-----------------|------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001041    | ETIM 7.0    | EC001041    |
| ECLASS 9.0  | 27-14-11-35 | ECLASS 9.1  | 27-14-11-35 |
| ECLASS 10.0 | 27-14-11-35 | ECLASS 11.0 | 27-14-11-35 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                             |                                                                            |
|-----------------------------|----------------------------------------------------------------------------|
| Engineering Data            | <a href="#">04520_EWK_1_DXF.dxf</a><br><a href="#">STEP</a>                |
| Engineering Data            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                   |
| Product Change Notification | <a href="#">Technical Change EN</a><br><a href="#">Technical Change DE</a> |
| User Documentation          | <a href="#">StorageConditionsTerminalBlocks</a>                            |