


**DK 4/35 LD GR 24VDC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| Version    | SAK Series, Double-tier terminal, Rated cross-section: 4 mm <sup>2</sup> , Screw connection, Direct mounting |
| Order No.  | <a href="#">0210460000</a>                                                                                   |
| Type       | DK 4/35 LD GR 24VDC                                                                                          |
| GTIN (EAN) | 4008190089405                                                                                                |
| Qty.       | 25 pc(s).                                                                                                    |

## DK 4/35 LD GR 24VDC

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 52.5 mm    | Depth (inches)  | 2.067 inch |
| Height         | 50 mm      | Height (inches) | 1.969 inch |
| Net weight     | 12.16 g    | Width           | 6 mm       |
| Width (inches) | 0.236 inch |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C         |                                  |        |

## Material data

|                           |       |        |                |
|---------------------------|-------|--------|----------------|
| Material                  | PA 66 | Colour | beige / yellow |
| UL 94 flammability rating | V-2   |        |                |

## System specifications

|                                     |                                                       |                               |     |
|-------------------------------------|-------------------------------------------------------|-------------------------------|-----|
| Version                             | Screw connection, with LED, One end without connector | End cover plate required      | Yes |
| Number of potentials                | 1                                                     | Number of levels              | 2   |
| Number of clamping points per level | 2                                                     | Number of potentials per tier | 1   |
| Levels cross-connected internally   | Yes                                                   | PE connection                 | No  |
| Rail                                | TS 35                                                 | N-function                    | No  |
| PE function                         | No                                                    | PEN function                  | No  |

## Additional technical data

|                     |                 |                             |         |
|---------------------|-----------------|-----------------------------|---------|
| Installation advice | Direct mounting | Number of similar terminals | 1       |
| Open sides          | right           | Type of mounting            | Snap-on |

## Conductors for clamping (rated connection)

|                                                                                         |                     |                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|---------------------|
| Blade size                                                                              | 0.6 x 3.5 mm        | Clamping range, max.                                                                    | 4 mm <sup>2</sup>   |
| Clamping range, min.                                                                    | 0.5 mm <sup>2</sup> | Clamping screw                                                                          | M 3                 |
| Connection cross-section, stranded, max.                                                | 4 mm <sup>2</sup>   | Connection cross-section, stranded, min.                                                | 0.5 mm <sup>2</sup> |
| Connection direction                                                                    | on side             | Gauge to IEC 60947-1                                                                    | A3                  |
| Number of connections                                                                   | 4                   | Stripping length                                                                        | 9 mm                |
| Tightening torque, max.                                                                 | 1 Nm                | Tightening torque, min.                                                                 | 0.5 Nm              |
| Torque level with DMS electric screwdriver                                              | 2                   | Type of connection                                                                      | Screw connection    |
| Wire connection cross section AWG, max.                                                 | AWG 12              | Wire connection cross section AWG, min.                                                 | AWG 22              |
| Wire connection cross section, finely stranded, max.                                    | 4 mm <sup>2</sup>   | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 mm <sup>2</sup>   |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm <sup>2</sup> | Wire connection cross-section, solid core, max.                                         | 4 mm <sup>2</sup>   |
| Wire connection cross-section, solid core, min.                                         | 0.5 mm <sup>2</sup> |                                                                                         |                     |

## Dimensions

|              |       |
|--------------|-------|
| TS 35 offset | 25 mm |
|--------------|-------|

Creation date March 22, 2021 9:03:38 AM CET

## DK 4/35 LD GR 24VDC

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Display element

|                                     |      |                                     |      |
|-------------------------------------|------|-------------------------------------|------|
| Current                             | 5 mA | Indicator element                   | red  |
| Operating voltage for display, max. | 24 V | Operating voltage for display, min. | 24 V |
| Type of voltage for indicator       | DC   |                                     |      |

## General

|                                         |                 |                                         |        |
|-----------------------------------------|-----------------|-----------------------------------------|--------|
| Installation advice                     | Direct mounting | Rail                                    | TS 35  |
| Standards                               | IEC 60947-7-1   | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 22          |                                         |        |

## Rating data

|                                             |               |                                              |                   |
|---------------------------------------------|---------------|----------------------------------------------|-------------------|
| Power loss in accordance with IEC 60947-7-x | 1.02 W        | Rated cross-section                          | 4 mm <sup>2</sup> |
| Rated voltage                               | 24 V          | Current at maximum wires                     | 10 A              |
| Standards                                   | IEC 60947-7-1 | Volume resistance according to IEC 60947-7-x | 1 mΩ              |
| Rated impulse withstand voltage             | 1 kV          | Pollution severity                           | 3                 |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ECLASS 9.0  | 27-14-11-20 | ECLASS 9.1  | 27-14-11-20 |
| ECLASS 10.0 | 27-14-11-20 | ECLASS 11.0 | 27-14-11-20 |

## Approvals

Approvals



ROHS

Conform

## Downloads

|                                             |                                                                                                                           |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a><br><a href="#">Declaration of Conformity</a><br><a href="#">Declaration of Conformity</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                                                              |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks</a>                                                                           |