

AP AST1+5 KRG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Version	SAK Series, End plate, 3 mm, dark beige, yellow, Direct mounting
Order No.	0266420000
Type	AP AST1+5 KRG
GTIN (EAN)	4008 190043483
Qty.	20 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2020-12-31
Alternative product	0266400000

Creation date March 22, 2021 9:41:42 AM CET

AP AST1+5 KRG

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 inch
Height	58 mm	Height (inches)	2.283 inch
Net weight	7.5 g	Width	3 mm
Width (inches)	0.118 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-60 °C
Continuous operating temp., max.	130 °C		

Material data

Material	KrG	Colour	dark beige, yellow
UL 94 flammability rating	V-0		

System specifications

Version	End plate
---------	-----------

Additional technical data

Installation advice	Direct mounting	Snap-on	Yes
---------------------	-----------------	---------	-----

General

Installation advice	Direct mounting
---------------------	-----------------

Classifications

ETIM 6.0	EC000886	ETIM 7.0	EC000886
ECLASS 9.1	27-14-11-33	ECLASS 10.0	27-14-11-33
ECLASS 11.0	27-14-11-33		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	02732_AP_AST1+5_KRG_DXF.dxf
Engineering Data	EPLAN_WSCAD
User Documentation	StorageConditionsTerminalBlocks