

**TS 35X15/2.3 2M/CU/BK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

**General ordering data**

|            |                                                          |
|------------|----------------------------------------------------------|
| Version    | Rail, TS 35, TS 35 x 15, without slot, Copper, untreated |
| Order No.  | <a href="#">0270100000</a>                               |
| Type       | TS 35X15/2.3 2M/CU/BK                                    |
| GTIN (EAN) | 4008190105136                                            |
| Qty.       | 2 m                                                      |

## TS 35X15/2.3 2M/CU/BK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 15 mm      | Depth (inches)  | 0.591 inch |
| Height         | 35 mm      | Height (inches) | 1.378 inch |
| Net weight     | 940 g      | Width           | 2,000 mm   |
| Width (inches) | 78.74 inch |                 |            |

## Mounting rail

|                                                         |                 |          |
|---------------------------------------------------------|-----------------|----------|
| Installation advice                                     | Direct mounting |          |
| Length of the terminal rail                             | min.            | 0 mm     |
|                                                         | max.            | 2,000 mm |
|                                                         | nominal         | 2,000 mm |
| Material                                                | Copper          |          |
| Permitted thermal current for PEN function, max.        | 309 A           |          |
| Pre-punched mounting rail                               | No              |          |
| Short circuit strength corresponds to E-Cu wire         | 150 mm²         |          |
| Short-time withstand current according to IEC 60947-7-2 | 18 kA/1s        |          |
| Slit gap                                                |                 |          |
| Slit length                                             |                 |          |
| Slit width                                              |                 |          |
| Standards                                               | DIN EN 60715    |          |
| Surface finish                                          | untreated       |          |
| Thickness                                               | 2.3 mm          |          |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001285    | ETIM 7.0    | EC001285    |
| ECLASS 9.0  | 27-40-06-02 | ECLASS 9.1  | 27-40-06-02 |
| ECLASS 10.0 | 27-40-06-02 | ECLASS 11.0 | 27-40-06-02 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                            |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |