

EP 2/BW SAKG46/32 HP/DB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Version	SAK Series, End plate, dark beige, 75.5 mm
Order No.	0271900000
Type	EP 2/BW SAKG46/32 HP/DB
GTIN (EAN)	4008190172497
Qty.	10 pc(s).

EP 2/BW SAKG46/32 HP/DB

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	90.5 mm	Depth (inches)	3.563 inch
Height	160 mm	Height (inches)	6.299 inch
Net weight	51.2 g	Width	75.5 mm
Width (inches)	2.972 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Material data

Material	Plastic	Colour	dark beige
UL 94 flammability rating	V-2		

System specifications

Version	with end bracket
---------	------------------

Additional technical data

Explosion-tested version	No	Interlock	for screw fixing
Type of fixing	when screwed in		

Dimensions

Pitch in mm (P)	160 mm	TS 32 offset	80 mm
-----------------	--------	--------------	-------

Classifications

ETIM 6.0	EC000886	ETIM 7.0	EC000886
ECLASS 9.0	27-14-11-33	ECLASS 9.1	27-14-11-33
ECLASS 10.0	27-14-11-33	ECLASS 11.0	27-14-11-33

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD
User Documentation	StorageConditionsTerminalBlocks