

**BS 25 IH/VI SAKT1****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | SAK Series, Set of fixings |
| Order No.  | <a href="#">0335800000</a> |
| Type       | BS 25 IH/VI SAKT1          |
| GTIN (EAN) | 4008190039196              |
| Qty.       | 50 pc(s).                  |

**BS 25 IH/VI SAKT1****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                 |            |                |            |
|-----------------|------------|----------------|------------|
| Depth           | 28.7 mm    | Depth (inches) | 1.13 inch  |
| Diameter        | 3 mm       | Height         | 5.5 mm     |
| Height (inches) | 0.217 inch | Net weight     | 1.74 g     |
| Width           | 5.5 mm     | Width (inches) | 0.217 inch |

**Temperatures**

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Material data**

|          |       |        |        |
|----------|-------|--------|--------|
| Material | Steel | Colour | violet |
|----------|-------|--------|--------|

**System specifications**

|         |                           |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

**Additional technical data**

|                     |                 |                  |                 |
|---------------------|-----------------|------------------|-----------------|
| Installation advice | Direct mounting | Type of mounting | when screwed in |
|---------------------|-----------------|------------------|-----------------|

**Dimensions**

|          |      |
|----------|------|
| Diameter | 3 mm |
|----------|------|

**General**

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002848    | ETIM 7.0    | EC002848    |
| ECLASS 9.0  | 27-14-11-92 | ECLASS 9.1  | 27-14-11-92 |
| ECLASS 10.0 | 27-14-11-92 | ECLASS 11.0 | 27-14-11-92 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                            |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |