

**H4,0/9****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)For conductors from 0.25 to 6,0 mm<sup>2</sup> (AWG 24 - 10)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in polybag

**General ordering data**

|            |                                     |
|------------|-------------------------------------|
| Version    | Wire-end ferrule, uninsulated, 9 mm |
| Order No.  | <a href="#">0373100000</a>          |
| Type       | H4,0/9                              |
| GTIN (EAN) | 4008190164669                       |
| Qty.       | 500 pc(s).                          |
| Packaging  | loose                               |

Creation date March 22, 2021 10:13:17 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**H4,0/9****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |        |
|------------|--------|
| Net weight | 0.13 g |
|------------|--------|

**Technical data**

|                        |                                         |         |             |
|------------------------|-----------------------------------------|---------|-------------|
| Description of article | Wire end ferrule without plastic collar | Version | uninsulated |
|------------------------|-----------------------------------------|---------|-------------|

**Wire-end ferrules**

|                               |        |                                         |                   |
|-------------------------------|--------|-----------------------------------------|-------------------|
| Collar diameter (D2)          | 4 mm   | Conductor cross-section                 | 4 mm <sup>2</sup> |
| Contact surface diameter (D1) | 2.8 mm | L1 in mm                                | 9 mm              |
| Stripping length              | 9 mm   | Wire connection cross section AWG, max. | AWG 12            |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">STEP</a>                     |
| Engineering Data | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |

**H4,0/9**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

