

SO SH1**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Shielding and earthing**

Our protective earth conductor and shielding terminals featuring different connection technologies allow you to effectively protect both people and equipment from interference, such as electrical or magnetic fields. A comprehensive range of accessories rounds off our range.

General ordering data

Version	Accessories, Rail support, Polyamide 66
Order No.	0401460000
Type	SO SH1
GTIN (EAN)	4008190188092
Qty.	20 pc(s).

SO SH1

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	20.6 mm	Depth (inches)	0.811 inch
Height	24.5 mm	Height (inches)	0.965 inch
Net weight	4.385 g	Width	24.5 mm
Width (inches)	0.965 inch		

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
----------------------------------	--------	----------------------------------	--------

Material data

Material	Polyamide 66	Colour	grey
UL 94 flammability rating	V-2		

System specifications

Version	For the mounting rails	Rail	TS 15
---------	------------------------	------	-------

Additional technical data

Type of mounting	when screwed in
------------------	-----------------

Conductors for clamping (rated connection)

Type of connection	Miscellaneous
--------------------	---------------

General

Rail	TS 15
------	-------

Classifications

ETIM 6.0	EC001166	ETIM 7.0	EC001166
ECLASS 9.0	27-40-06-07	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-40-06-07	ECLASS 11.0	27-40-06-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD
User Documentation	StorageConditionsTerminalBlocks