

**H0,75/12 W****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- supplied loose in polybag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                |
|------------|------------------------------------------------|
| Version    | Wire-end ferrule, insulated, 8 mm, 6 mm, white |
| Order No.  | <a href="#">0409600000</a>                     |
| Type       | H0,75/12 W                                     |
| GTIN (EAN) | 4008190079826                                  |
| Qty.       | 500 pc(s).                                     |
| Packaging  | loose                                          |

**H0,75/12 W****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |
|------------|---------|
| Net weight | 0.074 g |
|------------|---------|

**Technical data**

|                        |                                             |         |           |
|------------------------|---------------------------------------------|---------|-----------|
| Description of article | Wire end ferrule with plastic collar, white | Version | insulated |
|------------------------|---------------------------------------------|---------|-----------|

**Wire-end ferrules**

|                                         |                      |                               |             |
|-----------------------------------------|----------------------|-------------------------------|-------------|
| Collar diameter (D2)                    | 2.8 mm               | Colour code                   | Weidmüller  |
| Conductor cross-section                 | 0.75 mm <sup>2</sup> | Contact surface diameter (D1) | 1.2 mm      |
| Contact surface length (L2)             | 6 mm                 | L1 in mm                      | 12 mm       |
| Metal sleeve thickness (S1)             | 0.15 mm              | Military designation          | T 20A 004 A |
| Plastic collar thickness (S2)           | 0.25 mm              | Stripping length              | 8 mm        |
| Wire connection cross section AWG, max. | AWG 18               |                               |             |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">STEP</a>                     |
| Engineering Data | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |

**H0,75/12 W****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**