



Main

Range	Linergy
Product or component type	Distribution block
Product destination	Busbar
Accessory / separate part category	Connection accessory

Complementary

Product name	Linergy DP
Product compatibility	Spacial enclosures
Mounting mode	Plate
Cable cross section	35 mm ²
Poles description	3P
Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[Ie] rated operational current	250 A at 40 °C
Connections - terminals	1 screw terminal 35 mm ²
Quantity per set	Set of 3
Material	Metal
Product weight	0.235 kg

Environment

IP degree of protection	IPxx B
-------------------------	--------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------