

G 20/0.25A/F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Version	Active components, Fuse
Order No.	0430500000
Type	G 20/0.25A/F
GTIN (EAN)	4008 19015399 1
Qty.	10 pc(s).

G 20/0.25A/F

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	5 mm	Depth (inches)	0.197 inch
Height	20 mm	Height (inches)	0.787 inch
Net weight	0.9 g	Width	5 mm
Width (inches)	0.197 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Material data

Colour	Light Grey
--------	------------

System specifications

Version	Fuse accessories
---------	------------------

Fuse cartridges

Cartridge fuse	G-Si. 5 x 20	Characteristics	quick-acting
Colour	Light Grey	Current	0.25 A
Melting integral	0.07 A ² s	Optical function display	No
Power output (@ 1.5 In)	0.3 W	Rated breaking capacity	1.5 kA
Version	Fuse accessories	Voltage drop	280 mV

Rating data

Rated voltage	250 V	Rated current	0.25 A
---------------	-------	---------------	--------

Classifications

ETIM 6.0	EC000035	ETIM 7.0	EC000035
ECLASS 9.0	27-14-20-01	ECLASS 9.1	27-14-20-01
ECLASS 10.0	27-14-20-01	ECLASS 11.0	27-14-20-01

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN.WSCAD
User Documentation	StorageConditionsTerminalBlocks