

H0,75/10**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.comFor conductors from 0.25 to 6,0 mm² (AWG 24 - 10)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in polybag

General ordering data

Version	Wire-end ferrule, uninsulated, 10 mm
Order No.	0542500000
Type	H0,75/10
GTIN (EAN)	4008190037482
Qty.	1,000 pc(s).
Packaging	loose

Creation date March 22, 2021 10:50:42 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

H0,75/10**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	0.06 g
------------	--------

Technical data

Description of article	Wire end ferrule without plastic collar	Version	uninsulated
------------------------	---	---------	-------------

Wire-end ferrules

Collar diameter (D2)	2.3 mm	Conductor cross-section	0.75 mm ²
Contact surface diameter (D1)	1.2 mm	L1 in mm	10 mm
Stripping length	10 mm	Wire connection cross section AWG, max.	AWG 18

Classifications

ETIM 6.0	EC000005	ETIM 7.0	EC000005
ECLASS 9.0	27-40-02-01	ECLASS 9.1	27-40-02-01
ECLASS 10.0	27-40-02-01	ECLASS 11.0	27-40-02-01

Approvals

Approvals



ROHS	Conform
UL File Number Search	E499744

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S

H0,75/10

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

