

SAKG 32/35 II/GW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Version	SAK Series, Feed-through terminal, Rated cross-section: 50 mm², Screw connection, medium yellow
Order No.	0637420000
Type	SAKG 32/35 II/GW
GTIN (EAN)	4008190070564
Qty.	10 pc(s).

SAKG 32/35 II/GW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	53 mm	Depth (inches)	2.087 inch
Height	80 mm	Height (inches)	3.15 inch
Net weight	146.4 g	Width	32 mm
Width (inches)	1.26 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-60 °C
Continuous operating temp., max.	130 °C		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Material data

Material	KrG	Colour	medium yellow
UL 94 flammability rating	V-0, 5VA		

System specifications

Version	Stud terminal	End cover plate required	Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35	N-function	No
PE function	No	PEN function	No

Additional technical data

Explosion-tested version	No	Number of similar terminals	1
Open sides	Open	Type of mounting	Snap-on

CSA rating data

Certificate No. (CSA)	12400-199	Current size C (CSA)	170 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	00 AWG
Wire cross section min. (CSA)	1 AWG		

Conductors for clamping (rated connection)

Clamping range, max.	70 mm ²	Clamping range, min.	10 mm ²
Clamping screw	M 8	Connection direction	on side
Number of connections	1	Tightening torque, max.	12 Nm
Tightening torque, min.	6 Nm	Type of connection	Screw connection
Wire connection cross section AWG, max.	AWG 2/0	Wire connection cross section AWG, min.	AWG 1

General

Rail	TS 35	Standards	IEC 60947-7-1
Wire connection cross section AWG, max.	AWG 2/0	Wire connection cross section AWG, min.	AWG 1

SAKG 32/35 II/GW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Rating data

Power loss in accordance with IEC 60947-7-x

4.8 W

Rated voltage

1,000 V

Current at maximum wires

192 A

Volume resistance according to IEC 60947-7-x

0.21 mΩ

Pollution severity

3

Rated cross-section

50 mm²

Rated current

150 A

Standards

IEC 60947-7-1

Rated impulse withstand voltage

8 kV

UL rating data

Certificate No. (UR)

E60693

Conductor size Factory wiring min. (UR)

6 AWG

Conductor size Field wiring min. (UR)

6 AWG

Voltage size C (UR)

600 V

Conductor size Factory wiring max. (UR)

000 AWG

Conductor size Field wiring max. (UR)

000 AWG

Current size C (UR)

200 A

Classifications

ETIM 6.0

EC000897

ECLASS 9.0

27-14-11-20

ECLASS 10.0

27-14-11-20

ETIM 7.0

EC000897

ECLASS 9.1

27-14-11-20

ECLASS 11.0

27-14-11-20

Approvals

Approvals



ROHS

Conform

UL File Number Search

E60693

Downloads

Approval/Certificate/Document of Conformity

[EAC certificate](#)[MARITREG Certificate](#)[Declaration of Conformity](#)[Declaration of Conformity](#)

Engineering Data

[EPLAN, WSCAD](#)

User Documentation

[StorageConditionsTerminalBlocks](#)