

KSP L55 S**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

General ordering data

Version	KSP (Klippon shroud), Protective cap, Silicone
Order No.	0930700005
Type	KSP L55 S
GTIN (EAN)	4032248976003
Qty.	10 pc(s).

KSP L55 S**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Length	150 mm	Length (inches)	5.905 inch
Net weight	59.4 g		

General information

Gap, internal dimension B	85 mm	Hardness (IRHD)	60
Inside diameter D2	55 mm	Material	Silicone
O.D.	58 mm	Operating temperature range, max.	200 °C
Operating temperature range, min.	-60 °C	Thickness	1.5 mm

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-90
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD
------------------	------------------------------

KSP L55 S

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

