

HDC C HX SM4.0AG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

General ordering data

Version	Heavy-duty connectors, Crimp contact, MixMate, Pin, Conductor cross-section, max.: 4, turned, Copper alloy
Order No.	1002930000
Type	HDC C HX SM4.0AG
GTIN (EAN)	4032248697212
Qty.	25 pc(s).

HDC C HX SM4.0AG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Diameter	6 mm	Net weight	2.948 g
----------	------	------------	---------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Conductor cross-section, max.	4 mm ²	Contact diameter, male Ø	4 mm
Cross-section for connected wire	4 mm ²	Material	Copper alloy
Plugging cycles	≥ 500	Production methods	turned
Stripping length, rated connection	8 mm	Surface finish	silver
Type	Pin	Type of connection	Crimp connection
Version insert	MixMate	Volume resistance	≤1 mΩ

Classifications

ETIM 6.0	EC000796	ETIM 7.0	EC000796
ECLASS 9.0	27-44-02-04	ECLASS 9.1	27-44-02-04
ECLASS 10.0	27-44-02-04	ECLASS 11.0	27-44-02-04

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD

HDC C HX SM4.0AG

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

