

THM WO T 24.5/100 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

Version	THM, Conductor and cable markers, 8 - 23 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white
Order No.	1003380000
Type	THM WO T 24.5/100 WS
GTIN (EAN)	4032248699278
Qty.	1 pc(s).
compatible printer	2599430000 2599440000

Creation date March 22, 2021 12:38:44 PM CET

THM WO T 24.5/100 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.05 mm	Depth (inches)	0.002 inch
Height	24.5 mm	Height (inches)	0.965 inch
Net weight	838 g	Width	100 mm
Width (inches)	3.937 inch		

Temperatures

Operating temperature range	-40...107 °C
-----------------------------	--------------

General data

Adhesive	Polyacrylate adhesive	Approval acc. to UL 969	No
Colour	white	Halogen	Yes
Material	Tedlar polyvinyl fluoride film®	Material colour according to resistance code	9
Number of markers per combination	1 Label reel = Conductor and cable markers	Number per roll	2,000
Operating temperature range	-40...107 °C	Operating temperature range, max.	107 °C
Operating temperature range, min.	-40 °C	Size of labelling field	25 x 24.5 mm
Type of printing	neutral	UL 94 flammability rating	V-0
Version	Self-adhesive	Width	100 mm

Conductor and cable markers

Conductor O.D.	8 - 23 mm	Conductor O.D., max.	23 mm
Conductor O.D., min.	8 mm	Conductor cross-section, max.	120 mm ²
Cross-section for connected wire	120 mm ²	Halogen	Yes
Text field height	25 mm	Text field width	24.5 mm

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S

Data sheet

THM WO T 24.5/100 WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

