

Multiplexer - FB-MUX/HS/AI/PA - 1005331

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The FB-MUX/HS/AI/PA head station can be used with up to five 4-channel analog input modules (RAD-AI4-IFS), five 4-channel PT100 temperature sensing modules (PT100-4-IFS), or any combination of modules for a maximum of 20 channels. This configuration can be used as an analog input and temperature control solution.

Product Description

The fieldbus PA multiplexer headstation allows the integration of standard Radioline I/O modules to a Profibus PA network. The FB-MUX/HS/PA has five profile software versions for different IO configurations.

Your advantages

- ✓ IECEx CoC
- ✓ Suitable for ATEX Zone 2
- ✓ Connection of all I/O field signals with standard PROFIBUS PA cable
- ✓ UL listed
- ✓ No software needed thanks to a pre-configured head station
- ✓ Five application-specific head stations allow simple implementation in the field
- ✓ Easy integration into host system with an EDD-, GSD-, or DTM-data file
- ✓ Scalable according to application needs

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 475776
GTIN	4055626475776
Weight per Piece (excluding packing)	140.000 g
Custom tariff number	85176200
Country of origin	United States