

Multiplexer - FB-MUX/HS/DI24/PA - 1005332

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The FB-MUX/HS/DI24/PA head station can be used with up to six 4-channel digital input modules (RAD-DI4-IFS), six 4-channel NAMUR digital input modules (RAD-NAM4-IFS), three 8-channel digital input modules (RAD-DI8-IFS), or any combination of modules for maximum of 24 total channels. This configuration can be used as a high-density digital input solution.

Product Description

The fieldbus PA multiplexer headstation allows the integration of standard Radioline I/O modules to a Profibus PA network. The FB-MUX/HS/PA has five profile software versions for different IO configurations.

Your advantages

- ✓ Scalable according to application needs
- ✓ Five application-specific head stations allow simple implementation in the field
- ✓ Easy integration into host system with an EDD-, GSD-, or DTM-data file
- ✓ Connection of all I/O field signals with standard PROFIBUS PA cable
- ✓ No software needed thanks to a pre-configured head station
- ✓ IECEx CoC
- ✓ UL listed
- ✓ Suitable for ATEX Zone 2



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 475783
GTIN	4055626475783
Weight per Piece (excluding packing)	140.000 g
Custom tariff number	85176200
Country of origin	United States