

VGM63-SS 68 KB 34-44**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

General ordering data

Version	VG S (standard stainless steel cable gland), Cable glands, M 63, 14 mm, OD min. 34 - OD max. 44 mm, Stainless steel 1.4305 (303)
Order No.	1009910000
Type	VGM63-SS 68 KB 34-44
GTIN (EAN)	4032248714735
Qty.	5 pc(s).

VGM63-SS 68 KB 34-44

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	67 mm	Length (inches)	2.638 inch
Net weight	429.2 g		

Certificate numbers cable gland

Approval conditions	UL, DNV	Certificate no. cable gland (GERMLLOYD)	E-14047
Certificate no. cable gland (UL)	E-199260		

General information

AF size 1	65 mm	AF size 2	70 mm
Cable glands	metric	External thread	M 63
Length of thread	14 mm	Material	Stainless steel 1.4305 (303)
O-Ring	NBR	Operating temperature range, max.	100 °C
Operating temperature range, min.	-40 °C	Outer cable diameter, max.	44 mm
Outer cable diameter, min.	34 mm	Pitch of thread	1.5 mm
Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K	Seal insert	CR
Sealing	NBR	Tightening torque	50 Nm
Torque for cap nut, max.	55 Nm	Torque for cap nut, min.	45 Nm
Torque for connecting adapter, max.	60 Nm	Torque for connecting adapter, min.	70 Nm

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-32
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD