

**SAIBW-3/7****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

**General ordering data**

|            |                                                              |
|------------|--------------------------------------------------------------|
| Version    | Sockets prefabricated to customer spec., M12, Socket, angled |
| Order No.  | <a href="#">1021310000</a>                                   |
| Type       | SAIBW-3/7                                                    |
| GTIN (EAN) | 4032248734290                                                |
| Qty.       | 1 pc(s).                                                     |

## SAIBW-3/7

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |      |
|------------|------|
| Net weight | 24 g |
|------------|------|

## Environmental Product Compliance

|            |                                                      |
|------------|------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1,<br>Imidazolidine-2-thione<br>96-45-7 |
|------------|------------------------------------------------------|

## Technical data customisable plug-in connectors

|                                |                                |                                |                                       |
|--------------------------------|--------------------------------|--------------------------------|---------------------------------------|
| Cable diameter                 | 4...6 mm (PG7)/ 6...8 mm (PG9) | Cable diameter, max.           | 6 mm                                  |
| Cable diameter, min.           | 4 mm                           | Coding                         | A                                     |
| Conductor cross-section, max.  | 0.75 mm <sup>2</sup>           | Conductor cross-section, min.  | 0.14 mm <sup>2</sup>                  |
| Connection cross-section, max. | 0.75 mm <sup>2</sup>           | Connection cross-section, min. | 0.14 mm <sup>2</sup>                  |
| Contact surface                | CuSnZn                         | Housing main material          | PA                                    |
| Insulation strength            | 10 <sup>8</sup> Ω              | Number of poles                | 3                                     |
| Plugging cycles                | ≥ 50                           | Pollution severity             | 3                                     |
| Protection degree              | IP67                           | Rated current                  | 4 A                                   |
| Rated voltage                  | 250 V                          | Rated voltage (text)           | 250 V (3- and 4-pole) / 60 V (5-pole) |
| Shield connection              | No                             | Temperature range of housing   | -40 ... +85 °C                        |
| Threaded ring material         | Diecast zinc                   | Type of connection             | Screw connection                      |

## Standards

|                    |                 |
|--------------------|-----------------|
| Connector standard | IEC 61076-2-101 |
|--------------------|-----------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002635    | ETIM 7.0    | EC002635    |
| ECLASS 9.0  | 27-44-01-02 | ECLASS 9.1  | 27-44-01-03 |
| ECLASS 10.0 | 27-44-01-02 | ECLASS 11.0 | 27-44-01-02 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E307231 |

## Downloads

|                    |                        |
|--------------------|------------------------|
| Engineering Data   | <a href="#">STEP</a>   |
| Engineering Data   | <a href="#">WSCAD</a>  |
| User Documentation | <a href="#">Manual</a> |

## SAIBW-3/7

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Pole scheme

