

**DMC 12/27 MC SDR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

The DMC markers can be used for labelling switching devices or sub-assemblies. The large (12 x 27 mm) marking surface offers sufficient room for information describing the device and its function. Only one tag size for cable cross-sections from 0.5 – 10 mm<sup>2</sup> enables use on both multi-core control cables and single cores.

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

**General ordering data**

|                    |                                                                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Version            | DMC, Device markers, 1.5 - 7.5 mm,<br>{Reference (AttributeDefinition) not found:<br>pAttr74196859207437}, To customer<br>specification |
| Order No.          | <a href="#">1038830000</a>                                                                                                              |
| Type               | DMC 12/27 MC SDR                                                                                                                        |
| GTIN (EAN)         | 4032248768080                                                                                                                           |
| Qty.               | 10 pc(s).                                                                                                                               |
| compatible printer | <a href="#">2715590000</a> <a href="#">2438520000</a> <a href="#">2438510000</a>                                                        |

Creation date March 22, 2021 6:31:00 PM CET

**DMC 12/27 MC SDR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 5 mm       | Depth (inches)  | 0.197 inch |
| Height         | 12 mm      | Height (inches) | 0.472 inch |
| Net weight     | 1.67 g     | Width           | 27 mm      |
| Width (inches) | 1.063 inch |                 |            |

**Temperatures**

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...100 °C |
|-----------------------------|--------------|

**General data**

|                                   |                                                                      |                                   |                                                               |
|-----------------------------------|----------------------------------------------------------------------|-----------------------------------|---------------------------------------------------------------|
| Advice label                      | Colour based on customer requirements (Please send M-Print PRO file) | Colour                            | To customer specification                                     |
| Colour of printing                | black                                                                | Halogen                           | No                                                            |
| Material                          | Polyamide 66                                                         | Number of markers per combination | 1 MultiCard = Device markers                                  |
| Operating temperature range       | -40...100 °C                                                         | Operating temperature range, max. | 100 °C                                                        |
| Operating temperature range, min. | -40 °C                                                               | Printed characters                | Based on customer requirements (Please send M-Print PRO file) |
| Printing method                   | MC Laser                                                             | Width                             | 27 mm                                                         |

**Device markers**

|         |    |
|---------|----|
| Halogen | No |
|---------|----|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                             |
|------------------|-----------------------------|
| Engineering Data | <a href="#">EPLAN.WSCAD</a> |
|------------------|-----------------------------|