

**PAP PDU6/10 BL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

|                     |                                                                |
|---------------------|----------------------------------------------------------------|
| Version             | P-series, End plate, blue, 2.5 mm                              |
| Order No.           | <a href="#">1049200000</a>                                     |
| Type                | PAP PDU6/10 BL                                                 |
| GTIN (EAN)          | 4032248788330                                                  |
| Qty.                | 50 pc(s).                                                      |
| Delivery status     | <b>This article will no longer be available in the future.</b> |
| Available until     | 2023-03-31                                                     |
| Alternative product | <a href="#">1991950000</a>                                     |

Creation date March 22, 2021 8:58:01 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## PAP PDU6/10 BL

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 32.55 mm   | Depth (inches)  | 1.281 inch |
| Height         | 62.94 mm   | Height (inches) | 2.478 inch |
| Net weight     | 3.38 g     | Width           | 2.5 mm     |
| Width (inches) | 0.098 inch |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 120 °C         |                                  |        |

## Material data

|                           |       |        |      |
|---------------------------|-------|--------|------|
| Material                  | Wemid | Colour | blue |
| UL 94 flammability rating | V-0   |        |      |

## System specifications

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

## Additional technical data

|                     |                 |                  |                 |
|---------------------|-----------------|------------------|-----------------|
| Installation advice | Direct mounting | Type of mounting | Direct mounting |
|---------------------|-----------------|------------------|-----------------|

## General

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000886    | ETIM 7.0    | EC000886    |
| ECLASS 9.1  | 27-14-11-33 | ECLASS 10.0 | 27-14-11-33 |
| ECLASS 11.0 | 27-14-11-33 |             |             |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                            |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |