

ZTA ZDK 2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Accessories, Test adapter
Order No.	1052660000
Type	ZTA ZDK 2.5
GTIN (EAN)	4032248847891
Qty.	5 pc(s).

ZTA ZDK 2.5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	110.7 mm	Depth (inches)	4.358 inch
Height	35.6 mm	Height (inches)	1.402 inch
Net weight	22.2 g	Width	5.1 mm
Width (inches)	0.201 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	120		

Material data

Material	Wemid	Colour	black
UL 94 flammability rating	V-0		

System specifications

Version	For the terminals	Number of levels	1
Number of clamping points per level	1		

Additional technical data

With snap-in pegs	No
-------------------	----

Conductors for clamping (rated connection)

Number of connections	1	Tightening torque, max.	0.3 Nm
Tightening torque, min.	0.3 Nm		

Classifications

ETIM 6.0	EC002555	ETIM 7.0	EC002555
ECLASS 9.0	27-14-11-48	ECLASS 9.1	27-14-11-48
ECLASS 10.0	27-14-11-48	ECLASS 11.0	27-14-11-48

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EAC certificate
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
User Documentation	StorageConditionsTerminalBlocks