

**WQV 35/4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

**General ordering data**

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| Version    | W-Series, Cross-connector, For the terminals,<br>Number of poles: 4 |
| Order No.  | <a href="#">1055460000</a>                                          |
| Type       | WQV 35/4                                                            |
| GTIN (EAN) | 4008190130275                                                       |
| Qty.       | 50 pc(s).                                                           |

## WQV 35/4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 28 mm      | Depth (inches)  | 1.102 inch |
| Height         | 60.3 mm    | Height (inches) | 2.374 inch |
| Net weight     | 26.56 g    | Width           | 9.85 mm    |
| Width (inches) | 0.388 inch |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

## Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                     |                 |                |                 |
|---------------------|-----------------|----------------|-----------------|
| Installation advice | Direct mounting | Type of fixing | when screwed in |
|---------------------|-----------------|----------------|-----------------|

## Cross-connector

|                                          |              |                           |                 |
|------------------------------------------|--------------|---------------------------|-----------------|
| Number of cross-connected terminals      | 4            | Rated current, multi-pole | 112 A           |
| Tightening torque range for fixing screw | 1.2...2.4 Nm | Type                      | Cross-connector |

## Dimensions

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 16 mm |
|-----------------|-------|

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 4 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |     |               |       |
|---------------|-----|---------------|-------|
| Rated voltage | 400 | Rated current | 112 A |
|---------------|-----|---------------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ECLASS 9.0  | 27-14-11-40 | ECLASS 9.1  | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |

## Approvals

Approvals



ROHS

Conform

## WQV 35/4

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                                                          |
|---------------------------------------------|------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>                                                          |
| Engineering Data                            | <a href="#">09134_WQV_35-4_DXF.dxf</a><br><a href="#">STEP</a>                           |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation                          | <a href="#">Beipackzettel_WQV.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a> |