


**WDU 35/ZA OR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

**General ordering data**

|            |                                                                                     |
|------------|-------------------------------------------------------------------------------------|
| Version    | Feed-through terminal, Screw connection, 35 mm <sup>2</sup> , 1000 V, 125 A, orange |
| Order No.  | <a href="#">1060220000</a>                                                          |
| Type       | WDU 35/ZA OR                                                                        |
| GTIN (EAN) | 4032248812271                                                                       |
| Qty.       | 40 pc(s).                                                                           |

## WDU 35/ZA OR

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                          |            |                |            |
|--------------------------|------------|----------------|------------|
| Depth                    | 62.5 mm    | Depth (inches) | 2.461 inch |
| Depth including DIN rail | 63 mm      | Height         | 60 mm      |
| Height (inches)          | 2.362 inch | Net weight     | 53.525 g   |
| Weight                   | 54 g       | Width          | 16 mm      |
| Width (inches)           | 0.63 inch  |                |            |

## Temperatures

|                                  |                |                                  |                                                                                                   |
|----------------------------------|----------------|----------------------------------|---------------------------------------------------------------------------------------------------|
| Storage temperature              |                | Operating temperature range      | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity |
|                                  | -25 °C...55 °C |                                  |                                                                                                   |
| Continuous operating temp., min. | -60 °C         | Continuous operating temp., max. | 130 °C                                                                                            |

## Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | Wemid | Colour | orange |
| UL 94 flammability rating | V-0   |        |        |

## Rating data IECEx/ATEX

|                                |                                                                                                   |                                 |                    |
|--------------------------------|---------------------------------------------------------------------------------------------------|---------------------------------|--------------------|
| Certificate No. (ATEX)         | DEMKO14ATEX1338U                                                                                  | Certificate No. (IECEX)         | IECEXULD14.0005U   |
| Max. voltage (ATEX)            | 690 V                                                                                             | Current (ATEX)                  | 115 A              |
| Wire cross section max. (ATEX) | 35 mm <sup>2</sup>                                                                                | Max. voltage (IECEX)            | 690 V              |
| Current (IECEX)                | 115 A                                                                                             | Wire cross section max. (IECEX) | 35 mm <sup>2</sup> |
| Operating temperature range    | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity | Marking EN 60079-7              |                    |
|                                |                                                                                                   |                                 | Ex eb II C Gb      |
| Ex 2014/34/EU label            | II 2 G D                                                                                          |                                 |                    |

## System specifications

|                                     |                                                                                                |                               |     |
|-------------------------------------|------------------------------------------------------------------------------------------------|-------------------------------|-----|
| Version                             | Screw connection, for screwable cross-connection, With assembly peg, One end without connector | End cover plate required      |     |
|                                     |                                                                                                |                               | Yes |
| Number of potentials                | 1                                                                                              | Number of levels              | 1   |
| Number of clamping points per level | 2                                                                                              | Number of potentials per tier | 1   |
| Levels cross-connected internally   | No                                                                                             | PE connection                 | No  |
| Rail                                | TS 35                                                                                          | N-function                    | No  |
| PE function                         | No                                                                                             | PEN function                  | Yes |

## 2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

|                                                                                                            |                     |                                                                                                            |                     |
|------------------------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------|---------------------|
| Cross-section for connected wire, stranded, two clampable wires, max.                                      | 16 mm <sup>2</sup>  | Cross-section for connected wire, stranded, two clampable wires, min.                                      | 16 mm <sup>2</sup>  |
| Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, max. | 16 mm <sup>2</sup>  | Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, min. | 2.5 mm <sup>2</sup> |
| Wire connection cross section, finely stranded, two clampable wires, min.                                  | 2.5 mm <sup>2</sup> | Wire cross-section, finely stranded, two clampable wires, max.                                             | 16 mm <sup>2</sup>  |

## WDU 35/ZA OR

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Additional technical data

|                          |       |                             |         |
|--------------------------|-------|-----------------------------|---------|
| Explosion-tested version | Yes   | Number of similar terminals | 1       |
| Open sides               | right | Type of mounting            | Snap-on |

## CSA rating data

|                               |                |                               |       |
|-------------------------------|----------------|-------------------------------|-------|
| Certificate No. (CSA)         | 200039-1057876 | Current size C (CSA)          | 150 A |
| Voltage size C (CSA)          | 600 V          | Wire cross section max. (CSA) | 2 AWG |
| Wire cross section min. (CSA) | 12 AWG         |                               |       |

## Conductors for clamping (rated connection)

|                                          |                                        |                              |                       |       |  |
|------------------------------------------|----------------------------------------|------------------------------|-----------------------|-------|--|
| Blade size                               | 6.5 x 1.2 mm                           |                              |                       |       |  |
| Clampable conductor                      | Connection specification               |                              | Screw connection      |       |  |
|                                          | Cross-section for conductor connection | Type                         | solid, H05(07) V-U    |       |  |
|                                          |                                        | min.                         | 2.5 mm <sup>2</sup>   |       |  |
|                                          |                                        | max.                         | 16 mm <sup>2</sup>    |       |  |
|                                          |                                        | nominal                      | 35 mm <sup>2</sup>    |       |  |
|                                          | wire end ferrule                       | Stripping length             | min.                  | 18 mm |  |
|                                          |                                        |                              | max.                  | 18 mm |  |
|                                          |                                        |                              | nominal               | 18 mm |  |
|                                          |                                        | Tightening torque            | min.                  | 4 Nm  |  |
|                                          |                                        |                              | max.                  | 5 Nm  |  |
|                                          |                                        | Recommended wire-end ferrule |                       |       |  |
|                                          | Connection specification               |                              | Screw connection      |       |  |
|                                          | Cross-section for conductor connection | Type                         | stranded, H07V-R      |       |  |
|                                          |                                        | min.                         | 2.5 mm <sup>2</sup>   |       |  |
|                                          |                                        | max.                         | 50 mm <sup>2</sup>    |       |  |
|                                          |                                        | nominal                      | 35 mm <sup>2</sup>    |       |  |
|                                          | wire end ferrule                       | Stripping length             | min.                  | 18 mm |  |
|                                          |                                        |                              | max.                  | 18 mm |  |
|                                          |                                        |                              | nominal               | 18 mm |  |
|                                          |                                        | Tightening torque            | min.                  | 4 Nm  |  |
|                                          |                                        |                              | max.                  | 5 Nm  |  |
|                                          |                                        | Recommended wire-end ferrule |                       |       |  |
|                                          | Connection specification               |                              | Screw connection      |       |  |
|                                          | Cross-section for conductor connection | Type                         | flexible, H05(07) V-K |       |  |
|                                          |                                        | min.                         | 2.5 mm <sup>2</sup>   |       |  |
|                                          |                                        | max.                         | 35 mm <sup>2</sup>    |       |  |
|                                          |                                        | nominal                      | 35 mm <sup>2</sup>    |       |  |
| wire end ferrule                         | Stripping length                       | min.                         | 18 mm                 |       |  |
|                                          |                                        | max.                         | 18 mm                 |       |  |
|                                          |                                        | nominal                      | 18 mm                 |       |  |
|                                          | Tightening torque                      | min.                         | 4 Nm                  |       |  |
|                                          |                                        | max.                         | 5 Nm                  |       |  |
|                                          | Recommended wire-end ferrule           |                              |                       |       |  |
| Clamping range, max.                     | 50 mm <sup>2</sup>                     |                              |                       |       |  |
| Clamping range, min.                     | 2.5 mm <sup>2</sup>                    |                              |                       |       |  |
| Clamping screw                           | M 6                                    |                              |                       |       |  |
| Connection cross-section, stranded, max. | 50 mm <sup>2</sup>                     |                              |                       |       |  |
| Connection cross-section, stranded, min. | 2.5 mm <sup>2</sup>                    |                              |                       |       |  |
| Connection direction                     | on side                                |                              |                       |       |  |

Creation date March 22, 2021 9:42:04 PM CET

## WDU 35/ZA OR

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|
| Gauge to IEC 60947-1                                                                    | B8                  |
| Number of connections                                                                   | 2                   |
| Stripping length                                                                        | 18 mm               |
| Tightening torque, max.                                                                 | 5 Nm                |
| Tightening torque, min.                                                                 | 4 Nm                |
| Twin wire-end ferrules, max.                                                            | 16 mm <sup>2</sup>  |
| Twin wire-end ferrules, min.                                                            | 1.5 mm <sup>2</sup> |
| Type of connection                                                                      | Screw connection    |
| Wire connection cross section AWG, max.                                                 | AWG 2               |
| Wire connection cross section AWG, min.                                                 | AWG 12              |
| Wire connection cross section, finely stranded, max.                                    | 35 mm <sup>2</sup>  |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 35 mm <sup>2</sup>  |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 2.5 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 35 mm <sup>2</sup>  |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 2.5 mm <sup>2</sup> |
| Wire connection cross-section, solid core, max.                                         | 16 mm <sup>2</sup>  |
| Wire connection cross-section, solid core, min.                                         | 2.5 mm <sup>2</sup> |

## General

|                                         |       |                                         |               |
|-----------------------------------------|-------|-----------------------------------------|---------------|
| Rail                                    | TS 35 | Standards                               | IEC 60947-7-1 |
| Wire connection cross section AWG, max. | AWG 2 | Wire connection cross section AWG, min. | AWG 12        |

## Rating data

|                                              |         |                                 |                    |
|----------------------------------------------|---------|---------------------------------|--------------------|
| Power loss in accordance with IEC 60947-7-x  | 4 W     | Rated cross-section             | 35 mm <sup>2</sup> |
| Rated voltage                                | 1,000 V | Rated current                   | 125 A              |
| Current at maximum wires                     | 150 A   | Standards                       | IEC 60947-7-1      |
| Volume resistance according to IEC 60947-7-x | 0.26 mΩ | Rated impulse withstand voltage | 8 kV               |
| Pollution severity                           | 3       |                                 |                    |

## UL rating data

|                                         |        |                                         |         |
|-----------------------------------------|--------|-----------------------------------------|---------|
| Certificate No. (UR)                    | E60693 | Conductor size Factory wiring max. (UR) | 0 AWG   |
| Conductor size Factory wiring min. (UR) | 12 AWG | Conductor size Field wiring max. (UR)   | 0 AWG   |
| Conductor size Field wiring min. (UR)   | 12 AWG | Current size C (UR)                     | 150 A   |
| UL_current_Print                        | 150 A  | UL_voltage_Print                        | 1,000 V |
| UL_wire_max_Print                       | 0 AWG  | UL_wire_min_Print                       | 12 AWG  |
| Voltage size C (UR)                     | 1000 V |                                         |         |

## WDU 35/ZA OR

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ECLASS 9.0  | 27-14-11-20 | ECLASS 9.1  | 27-14-11-20 |
| ECLASS 10.0 | 27-14-11-20 | ECLASS 11.0 | 27-14-11-20 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

## Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">IECEX Certificate</a><br><a href="#">CB Testreport</a><br><a href="#">CB Certificate</a><br><a href="#">EAC certificate</a><br><a href="#">DNVGL certificate</a><br><a href="#">NEMKO certificate</a><br><a href="#">Lloyds Register Certificate</a><br><a href="#">MARITREG Certificate</a><br><a href="#">EAC EX Certificate</a><br><a href="#">CCC Ex Certificate</a><br><a href="#">ATEX Certificate</a> |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                                                                                                                                                                                                                                                     |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                                                                                                                                                                                                                                                                                                                                                 |
| User Documentation                          | <a href="#">NTI WDU/WPE 35.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a>                                                                                                                                                                                                                                                                                                                                    |

### WDU 35/ZA OR

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

