

Power supply unit - EM-CPS-PS/3AC/24DC/5 - 1064922

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Primary-switched power supply unit, TRIO POWER, Snap-on connection, Cross Power System - installation, input: 3-phase, output: 24 V DC / 5 A

Product Description

The TRIO CROSS POWER power supply for the CrossPowerSystem power distribution board is perfectly adapted for use in machine building. All of the functions and space-saving design are tailored to the high requirements in this area. The push-in connection enables quick and easy connection of a 24 V DC control voltage.

Your advantages

- ✓ Push-in connections for easy 24 V DC control voltage connection
- ✓ Fast startup: Tool-free mounting and automatic contacting in just one step (CrossPowerSystem)
- ✓ Reliable startup of high loads, thanks to the dynamic boost
- ✓ Electrically robust, thanks to high electric strength
- ✓ Maximum flexibility, thanks to the temperature range of -25°C... +70°C and device startup at -40°C



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 725222
GTIN	4055626725222
Weight per Piece (excluding packing)	780.000 g
Custom tariff number	85044030
Country of origin	China