

**WZAF 300****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Klippon® Connect with stud Technology**

Our stud terminals are an established, robust connection alternative for particularly harsh environments. The extensive accessories and quality workmanship ensure high productivity in planning and installation – and sustainable safety in operation..

**General ordering data**

|            |                                 |
|------------|---------------------------------|
| Version    | W-Series, Additional connection |
| Order No.  | <a href="#">1066500000</a>      |
| Type       | WZAF 300                        |
| GTIN (EAN) | 4008190157579                   |
| Qty.       | 10 pc(s).                       |

**WZAF 300****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 10 mm      | Depth (inches)  | 0.394 inch |
| Height         | 40 mm      | Height (inches) | 1.575 inch |
| Net weight     | 15.15 g    | Width           | 40 mm      |
| Width (inches) | 1.575 inch |                 |            |

**Temperatures**

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

**Material data**

|          |               |        |             |
|----------|---------------|--------|-------------|
| Material | tinned copper | Colour | Silver grey |
|----------|---------------|--------|-------------|

**System specifications**

|         |                       |
|---------|-----------------------|
| Version | Additional connection |
|---------|-----------------------|

**Additional technical data**

|                          |         |                     |                                            |
|--------------------------|---------|---------------------|--------------------------------------------|
| Explosion-tested version | No      | Installation advice | Feed-through (bushing),<br>Direct mounting |
| Type of fixing           | Snap-on |                     |                                            |

**Dimensions**

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 27 mm |
|-----------------|-------|

**General**

|                     |                                            |
|---------------------|--------------------------------------------|
| Installation advice | Feed-through (bushing),<br>Direct mounting |
|---------------------|--------------------------------------------|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002848    | ETIM 7.0    | EC002848    |
| ECLASS 9.0  | 27-14-11-92 | ECLASS 9.1  | 27-14-11-92 |
| ECLASS 10.0 | 27-14-11-92 | ECLASS 11.0 | 27-14-11-92 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">STEP</a>  |
| Engineering Data | <a href="#">EPLAN</a> |