

Q 2 WDL2.5S**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

| | |
|------------|---|
| Version | W-Series, Cross-connector, For the terminals, Number of poles: 2 |
| Order No. | 1071500000 |
| Type | Q 2 WDL2.5S |
| GTIN (EAN) | 4008 190424930 |
| Qty. | 50 pc(s). |

Creation date March 22, 2021 10:35:03 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

Data sheet

Q 2 WDL2.5S

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|----------------|------------|-----------------|------------|
| Depth | 9.5 mm | Depth (inches) | 0.374 inch |
| Height | 10.1 mm | Height (inches) | 0.398 inch |
| Net weight | 1.64 g | Width | 4 mm |
| Width (inches) | 0.157 inch | | |

Temperatures

| | |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Material data

| | | | |
|----------|---------------|--------|--------|
| Material | tinned copper | Colour | yellow |
|----------|---------------|--------|--------|

System specifications

| | |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|--|
| Explosion-tested version | No | Installation advice | Feed-through (bushing), Direct mounting |
| Type of fixing | when screwed in | | |

Dimensions

| | |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

General

| | | | |
|---------------------|--|-----------------|---|
| Installation advice | Feed-through (bushing), Direct mounting | Number of poles | 2 |
|---------------------|--|-----------------|---|

Rating data

| | |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ECLASS 9.0 | 27-14-11-40 | ECLASS 9.1 | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |

Approvals

Approvals



| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Creation date March 22, 2021 10:35:03 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

Data sheet**Q 2 WDL2.5S**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

| | |
|---|---|
| Approval/Certificate/Document of Conformity | EAC certificate |
| Engineering Data | STEP |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| User Documentation | StorageConditionsTerminalBlocks |
