

BG GHDE HO SA UL PT6**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The FieldPower® housings are highly robust and meet the highest UL flammability class 5 VA.

- The "TS 35 PT6" mounting rail module and PT6 contact unit are easy to snap on.
- Hinged seals allow pre-assembled plug cables to also be used.
- The high cover versions enable the device to be installed.

For cable seals consult accessories.

General ordering data

Version	FieldPower® Box, IP65 with corresponding housing, Polycarbonate, GF 10
Order No.	1113120000
Type	BG GHDE HO SA UL PT6
GTIN (EAN)	4032248891887
Qty.	1 pc(s).

BG GHDE HO SA UL PT6**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Depth	122 mm	Depth (inches)	4.803 inch
Height	181 mm	Height (inches)	7.126 inch
Net weight	684 g	Width	104 mm
Width (inches)	4.094 inch		

Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...45 °C
---------------------	----------------	-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Classifications

ETIM 6.0	EC000747	ETIM 7.0	EC000747
ECLASS 9.0	27-18-22-04	ECLASS 9.1	27-18-92-90
ECLASS 10.0	27-18-22-04	ECLASS 11.0	27-18-22-04

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	FieldPower
---	----------------------------

BG GHDE HO SA UL PT6

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Drilling template

