

FAD S7/300 HE40 UNIV**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Front adapters for Siemens S7-300 20- and 40-pole cards. The power can be supplied directly to the front adapter and it can be commonly or individually distributed per byte (8 signals).

General ordering data

Version	Interface, FAD, universal, Plug-in connectors according to IEC 60603-13 / DIN 41651 40p
Order No.	1127870000
Type	FAD S7/300 HE40 UNIV
GTIN (EAN)	4032248909513
Qty.	1 pc(s).

FAD S7/300 HE40 UNIV

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	115 mm	Length (inches)	4.528 inch
Net weight	1,035.29 g	Width	21.5 mm
Width (inches)	0.846 inch		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connection data

Connection (field side)	Plug-in connectors according to IEC 60603-13 / DIN 41651 40p	Connection to PLC	Siemens S7-300
Connection to the card	Siemens S7-300 card with 40-pole connector and operating voltage of ≤ 30 VAC / 60 VDC		

Ratings data

Operating voltage	30 V AC / 60 V DC	Max. current per channel	1 A
Total operating current	40 A		

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Pulse voltage test (1,2/50µs)	0.5 kV	Insulation test voltage	0.35 kVAC

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ECLASS 9.0	27-33-02-92	ECLASS 9.1	27-24-22-92
ECLASS 10.0	27-33-02-92	ECLASS 11.0	27-33-02-92

Approvals

Approvals



ROHS

Conform

FAD S7/300 HE40 UNIV

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

