

FAD CTLX HE20 UNIV**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Front adapter for Control-Logix card from Rockwell with 20- and 36-pole connectors. The power can be supplied directly to the front adapter and it can be commonly or individually distributed per byte (8 signals).

General ordering data

Version	Interface, FAD, universal, Plug-in connectors according to IEC 60603-13 / DIN 41651 20p
Order No.	1127900000
Type	FAD CTLX HE20 UNIV
GTIN (EAN)	4032248909285
Qty.	1 pc(s).
Delivery status	Discontinued
Available until	2019-10-31

Creation date March 23, 2021 1:16:25 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

FAD CTLX HE20 UNIV

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	34.5 mm	Length (inches)	1.358 inch
Net weight	20 g	Width	110 mm
Width (inches)	4.331 inch		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Connection data

Connection (field side)	Plug-in connectors according to IEC 60603-13 / DIN 41651 20p	Connection to PLC	Rockwell Control-Logix
Connection to the card	Control Logix card with 20-pole connector and operating voltage of ≤ 30 VAC / 60 VDC		

Ratings data

Operating voltage	30 V AC / 60 V DC	Max. current per channel	1 A
Total operating current	20 A		

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Pulse voltage test (1,2/50µs)	0.5 kV	Insulation test voltage	0.35 kVAC

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ECLASS 9.0	27-33-02-92	ECLASS 9.1	27-24-22-92
ECLASS 10.0	27-33-02-92	ECLASS 11.0	27-33-02-92

Approvals

Approvals



ROHS

Conform

FAD CTLX HE20 UNIV

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

