

## KSG M63 BS O NI 2 G63

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

### Similar to illustration



The KSG is only intended for use when connecting non-armoured cables and lines. When the cable gland is ordered together with a neoprene seal, the seal allows temperatures from  $-35^{\circ}\text{C}$  to  $+90^{\circ}\text{C}$ . When using a silicone seal, a temperature range of  $-60^{\circ}\text{C}$  to  $+180^{\circ}\text{C}$  is possible. The O-ring and the cable gland included in the delivery are made from the same material. IP66 or IP68 protection at a depth of 25 metres under water (a pressure of 2.5 bar) is guaranteed when using this sealing material. The KSG is permitted for use with pressure-resistant Ex d encapsulations and increased safety Ex e.

### General ordering data

Version	KSG (Klippon standard Ex cable gland), Cable glands, M 63, 19 mm, OD min. 46.7 - OD max. 56 mm, IP66, IP68 - 2.5 bar, Brass, nickel-plated
Order No.	<a href="#">1136690000</a>
Type	KSG M63 BS O NI 2 G63
GTIN (EAN)	4032248968213
Qty.	1 pc(s).

Creation date March 23, 2021 1:35:23 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## KSG M63 BS O NI 2 G63

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Length	37 mm	Length (inches)	1.457 inch
Net weight	877 g		

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

## Certificate numbers cable gland

Approval conditions	ATEX, IECEX, EAC	Certificate No. (ATEX)	SIRA05ATEX1287X
Certificate No. (IECEX)	IECEXSIR05.0067X	Certificate no. cable gland (EAC)	RU C-DE.HA65.B.00568 20
Identification	ATEX: II 2GD, Ex db IIC Gb, Ex ta IIIC Da and/or II 2 GD, Ex eb IIC Gb, Ex ta IIIC Da, IECEX: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da		

## General information

AF size 1	80 mm	Cable glands	metric, nickel-plated brass
Explosion protection type	Pressure-resistant Ex d encapsulation, Improved safety Ex e	External thread	M 63
Installation guidelines	See assembly instructions	Length of thread	19 mm
Material	Brass, nickel-plated	O-Ring	Silicone
Operating temperature range, max.	180 °C	Operating temperature range, min.	-60 °C
Outer cable diameter, max.	56 mm	Outer cable diameter, min.	46.7 mm
Pitch of thread	1.5 mm	Protection degree	IP66, IP68 - 2.5 bar
Protection degree with GWDR	IP66, IP68 - 2.5 bar	Seal insert	Silicone
Sealing	Silicone	Size of protective cap	L80
Water depth	25 m (30 Min.)		

## Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-34
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

## Approvals

Approvals



Approvals	EAC; ATEX; IECEX
ROHS	Conform

Creation date March 23, 2021 1:35:23 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

2

**KSG M63 BS O NI 2 G63****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Downloads**

Approval/Certificate/Document of Conformity	<a href="#">IECEXSIR05.0067X</a> <a href="#">SIRA05ATEX1287X</a> <a href="#">RU C-DE.HA65.B.00568 20</a> <a href="#">EU Declaration of Conformity - Klippon KSG cable Gland - DoC DE PS2680 160315 004ISS01</a>
Engineering Data	<a href="#">STEP</a>
Engineering Data	<a href="#">EPLAN_WSCAD</a>
User Documentation	<a href="#">Assembly guidelines</a>