

**KDSU M63 BS O SC 2 G63**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**


The KDSU features a special ring in the shape of a truncated cone. The ring enables connections between single-wire-armoured and metal-foil-armoured cables and braided-armoured lines. This ensure a conductive connection between the cable and the cable gland. It is also possible to connect non-armoured cables and lines. In addition, the KDSU comes with two separate seals which provide sealing for the outer and inner parts of the cable insulation. The cable armouring is located between the inner and outer insulation. When the cable gland is ordered together with a neoprene seal, the seal allows temperatures from -35°C to +90°C. When using a silicone seal, a temperature range of -60°C to +180°C is possible. The O-ring and the cable gland included in the delivery are made from the same material. When using both sealing materials, IP66 or IP68 protection at a depth of 25 metres under water (a pressure of 2.5 bar) is guaranteed. The KDSU is permitted for use with pressure-resistant Ex d encapsulations and increased safety Ex e. Besides the mechanical protective function offered for cables and lines, this can also be used for EMC applications.

**General ordering data**

|            |                                                                                                                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | KDSU (Klippon double seal universal Ex cable gland), Cable glands, M 63, 19 mm, Single-wire armouring, Metal foil armouring, Braided armouring, 0.1 - 2.5 mm, OD min. 58.4 - OD max. 65.8 mm, ID min. 46.70 - ID max. 56.00 mm, IP66, IP68 - 2.5 bar, Brass |
| Order No.  | <a href="#">1136950000</a>                                                                                                                                                                                                                                  |
| Type       | KDSU M63 BS O SC 2 G63                                                                                                                                                                                                                                      |
| GTIN (EAN) | 4032248969715                                                                                                                                                                                                                                               |
| Qty.       | 1 pc(s).                                                                                                                                                                                                                                                    |

## KDSU M63 BS 0 SC 2 G63

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Length     | 125 mm  | Length (inches) | 4.921 inch |
| Net weight | 2,290 g |                 |            |

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## Certificate numbers cable gland

|                         |                                                                                                                             |                                   |                            |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------------|----------------------------|
| Approval conditions     | ATEX, IECEX, EAC                                                                                                            | Certificate No. (ATEX)            | SIRA05ATEX1285X            |
| Certificate No. (IECEX) | IECEXSIR05.0067X                                                                                                            | Certificate no. cable gland (EAC) | RU C-DE.HA65.B.00568<br>20 |
| Identification          | ATEX: II 2G, Ex db IIC Gb,<br>Ex eb IIC Gb, II 1D, Ex ta<br>IIIC Da, IECEX: Ex db IIC<br>Gb, Ex eb IIC Gb, Ex ta IIIC<br>Da |                                   |                            |

## General information

|                                   |                      |                                   |                                                                      |
|-----------------------------------|----------------------|-----------------------------------|----------------------------------------------------------------------|
| AF size 1                         | 80 mm                | Armour, max.                      | 2.5 mm                                                               |
| Armour, min.                      | 0.1 mm               | Cable glands                      | metric, brass                                                        |
| External thread                   | M 63                 | Inner cable diameter, max.        | 56 mm                                                                |
| Inner cable diameter, min.        | 46.7 mm              | Installation guidelines           | See assembly instructions                                            |
| Length of thread                  | 19 mm                | Material                          | Brass                                                                |
| O-Ring                            | Silicone             | Operating temperature range, max. | 180 °C                                                               |
| Operating temperature range, min. | -60 °C               | Outer cable diameter, max.        | 65.8 mm                                                              |
| Outer cable diameter, min.        | 58.4 mm              | Pitch of thread                   | 1.5 mm                                                               |
| Protection degree                 | IP66, IP68 - 2.5 bar | Protection degree with GWDR       | IP66, IP68 - 2.5 bar                                                 |
| Seal insert                       | Silicone             | Sealing                           | Silicone                                                             |
| Size of protective cap            | EL80                 | Type of armouring                 | Single-wire armouring,<br>Metal foil armouring,<br>Braided armouring |
| Type of armouring, short term     | SWA, STA, SWB        | Water depth                       | 25 m (30 Min.)                                                       |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000441    | ETIM 7.0    | EC000441    |
| ECLASS 9.0  | 27-14-44-32 | ECLASS 9.1  | 27-14-44-34 |
| ECLASS 10.0 | 27-14-44-32 | ECLASS 11.0 | 27-14-44-32 |

## Approvals

Approvals



|           |                  |
|-----------|------------------|
| Approvals | EAC; ATEX; IECEX |
| ROHS      | Conform          |

## KDSU M63 BS 0 SC 2 G63

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                                                                                                                                                                                           |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">SIRA05ATEX1285X</a><br><a href="#">IECEXSIR05.0067X</a><br><a href="#">RU C-DE.HA65.B.00568 20</a><br><a href="#">EU Declaration of Conformity - Klippon KDSU cable Gland - DoC DE PS2680 160315 001ISS01</a> |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                                                      |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                                                                                                                                                              |
| User Documentation                          | <a href="#">Notice to Installers</a><br><a href="#">Assembly guidelines</a>                                                                                                                                               |