

KT 14**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

Version	Cutting tools, Cutting tool for one-hand operation
Order No.	1157820000
Type	KT 14
GTIN (EAN)	4032248945344
Qty.	1 pc(s).

KT 14

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 inch
Height	63.5 mm	Height (inches)	2.5 inch
Net weight	324.78 g	Weight	320 g
Width	225 mm	Width (inches)	8.858 inch

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Description of article	Cutting tool for up to 14 mm outside diameter	Version	One-hand mechanical
------------------------	---	---------	---------------------

Cutting tools

Copper cable - flexible, max.	70 mm ²	Copper cable - flexible, max. (AWG)	2/0 AWG
Copper cable - solid, max.	16 mm ²	Copper cable - solid, max. (AWG)	6 AWG
Copper cable - stranded, max.	35 mm ²	Copper cable - stranded, max. (AWG)	2 AWG
Copper cable, max. diameter	14 mm	Data / telephone / control cable, max. Ø	14 mm
Single-core aluminium cable, max.(mm ²)	35 mm ²	Stranded aluminium cable, max (mm ²)	70 mm ²
Stranded aluminium cable, max. (AWG)	2/0 AWG	Stranded aluminium cable, max. diameter	14 mm

Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
ECLASS 9.0	21-04-47-01	ECLASS 9.1	21-04-37-06
ECLASS 10.0	21-04-47-01	ECLASS 11.0	21-04-47-01

Approvals

Approvals



Downloads

Approval/Certificate/Document of Conformity

[Manufacturer's Declaration - Cable cutters](#)

KT 14

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings



max. 14 mm



max. 16 mm²



max. 35 mm²



max. 70 mm²