

**RF RS 70 LI/A2/O.SG BK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The RS 70 profile is supplied in fixed lengths. The desired length is obtained by connecting the individual pieces together. The PCB is pushed into the side of the profile. End cover plates close off the sides of the profile.. Elements for terminal rails and direct mounting are available here. The clip-on feet are permanently attached to the profile. Marking options are integrated into the side pieces.

**General ordering data**

|            |                                                        |
|------------|--------------------------------------------------------|
| Version    | Electronics housings black, Clip-in foot, Width: 10 mm |
| Order No.  | <a href="#">1162890000</a>                             |
| Type       | RF RS 70 LI/A2/O.SG BK                                 |
| GTIN (EAN) | 4032248960606                                          |
| Qty.       | 20 pc(s).                                              |

## RF RS 70 LI/A2/O.SG BK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Height         | 33.5 mm    | Height (inches) | 1.319 inch |
| Length         | 70 mm      | Length (inches) | 2.756 inch |
| Net weight     | 5.1 g      | Width           | 10 mm      |
| Width (inches) | 0.394 inch |                 |            |

## General data

|                      |       |                        |          |
|----------------------|-------|------------------------|----------|
| Colour               | black | Colour chart (similar) | RAL 9011 |
| Encapsulation option | No    | Protection degree      | IP20     |

## Material data

|                                  |       |                     |       |
|----------------------------------|-------|---------------------|-------|
| Comparative Tracking Index (CTI) | ≥ 600 | Insulating material | PA 66 |
| UL 94 flammability rating        | V-2   |                     |       |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002779    | ETIM 7.0    | EC002779    |
| ECLASS 9.0  | 27-18-27-90 | ECLASS 9.1  | 27-18-27-90 |
| ECLASS 10.0 | 27-18-27-92 | ECLASS 11.0 | 27-18-27-92 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|