

VREL 4 ZRV2.5/4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Version	Z-series, Locking element
Order No.	1167900000
Type	VREL 4 ZRV2.5/4
GTIN (EAN)	4032248959563
Qty.	10 pc(s).
Delivery status	Discontinued
Available until	2018-12-13

VREL 4 ZRV2.5/4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	22.2 mm	Depth (inches)	0.874 inch
Height	8.45 mm	Height (inches)	0.333 inch
Net weight	1.6 g	Width	10.3 mm
Width (inches)	0.406 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	130		

Material data

Material	PA 66 GF 30	Colour	black
UL 94 flammability rating	V-0		

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	WSCAD
User Documentation	StorageConditionsTerminalBlocks