

MTA 30 BK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Due to the wide range of variants with output voltages of 5, 12, 24, and 48 V and extensive international approvals, they are suitable for use in many applications. The power range extends from 35 W to 350 W. The individual adaptability makes PRO-PM the right choice for many standard machines.

General ordering data

Version	Electronics housings, Mounting flange, Accessories
Order No.	1168970000
Type	MTA 30 BK
GTIN (EAN)	4032248960965
Qty.	45 pc(s).

MTA 30 BK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Height	8 mm	Height (inches)	0.315 inch
Length	68 mm	Length (inches)	2.677 inch
Net weight	20.089 g	Weight	21.58 g
Width	30 mm	Width (inches)	1.181 inch

General data

Weight	21.58 g
--------	---------

Classifications

ETIM 6.0	EC002625	ETIM 7.0	EC002625
ECLASS 9.0	27-18-28-07	ECLASS 9.1	27-04-92-90
ECLASS 10.0	27-18-28-07	ECLASS 11.0	27-18-28-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN

MTA 30 BK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

