

IE-FPOD2UE-MW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Bulk stock, FO cable, POF

General ordering data

Version	Dragline cable, Break-out dragline, 980 µm, PUR, Products sold by meter, from 50 m
Order No.	1172280000
Type	IE-FPOD2UE-MW
GTIN (EAN)	4032248964437
Qty.	1 m
Delivery status	This article will no longer be available in the future.
Available until	2021-01-31

Creation date March 23, 2021 7:32:52 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-FPOD2UE-MW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	46 g
------------	------

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-40 °C...85 °C
Installation temperature	-30 °C...60 °C		

Technical specifications for cable

Bending cycles	6 Mio	Halogen	No
Number of wires	2	Sheathing colour	black

Cable structure

Cable layout	Break-out dragline	Core diameter	980 µm
Diameter of wire pair	2.2 mm	Material sheath	PUR
Number of wires	2	Primary coating	245 µm
Sheath diameter	7,5 mm	Sheath diameter, max.	8 mm
Sheathing colour	black		

Mechanical and material properties of cable

Bending cycles	6 Mio	Colour	black
Halogen	No	Min. bending radius, once only	25 mm
Min. bending radius, repetitive	60 mm		

Classifications

ETIM 6.0	EC000034	ETIM 7.0	EC000034
ECLASS 9.0	27-06-18-03	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-18-03	ECLASS 11.0	27-06-18-03

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN
--------------------	--

IE-FPOD2UE-MW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

Detailed drawing

