

BZT PRV16 SW 35X7.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****DCS marshalling**

Our innovative PRV terminal blocks for DCS marshalling featuring a PUSH IN connection and our multifunctional DCS marshalling terminals featuring a screw connection (WMF) not only save space in the panel; they also guarantee more effective signal transmission in process control systems.

General ordering data

Version	P-series, Marker holder, black, Number of levels: 16, TS 35 x 7.5
Order No.	1173550000
Type	BZT PRV16 SW 35X7.5
GTIN (EAN)	4032248966219
Qty.	20 pc(s).

BZT PRV16 SW 35X7.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	105.9 mm	Depth (inches)	4.169 inch
Height	225 mm	Height (inches)	8.858 inch
Net weight	50.72 g	Width	10.2 mm
Width (inches)	0.402 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	125 °C		

Material data

Material	Polycarbonate	Colour	black
UL 94 flammability rating	V-0		

System specifications

Version	For the mounting rails	Number of levels	16
Number of clamping points per level	2	Rail	TS 35 x 7.5

Conductors for clamping (rated connection)

Number of connections	32
-----------------------	----

General

Rail	TS 35 x 7.5
------	-------------

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks