


HBT 2,5 - 4,6 BL**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The use of insulated connectors guarantees users a permanent and consistent quality for their electrical connections.

In addition, they bring advantages during installation.

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² - 2.5 mm ² , blue
Order No.	1233330000
Type	HBT 2,5 - 4,6 BL
GTIN (EAN)	4050118016901
Qty.	100 pc(s).

HBT 2,5 - 4,6 BL**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	1.05 g
------------	--------

Technical data

Description of article	isolated hook-blade cable lug
------------------------	-------------------------------

Connectors

Conductor cross-section, max.	2.5 mm ²	Conductor cross-section, min.	1.5 mm ²
Identification colour	blue	Insulation	Available
Material/plastic	PC		

Dimensions

Hook nose X	2.1 mm	Insulation cross-section	4.5 mm
Length L	28.2 mm	Pin length P	17.4 mm
Pin width B	4.6 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------