


HBT 1,5 - 4,6 RT**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The use of insulated connectors guarantees users a permanent and consistent quality for their electrical connections.

In addition, they bring advantages during installation.

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 0.5 mm ² - 1.5 mm ² , red
Order No.	1233340000
Type	HBT 1,5 - 4,6 RT
GTIN (EAN)	4050118210972
Qty.	100 pc(s).

HBT 1,5 - 4,6 RT**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	1 g
------------	-----

Technical data

Description of article	isolated hook-blade cable lug
------------------------	----------------------------------

Connectors

Conductor cross-section, max.	1.5 mm ²	Conductor cross-section, min.	0.5 mm ²
Identification colour	red	Insulation	Available
Material/plastic	PC		

Dimensions

Hook nose X	2.1 mm	Insulation cross-section	4 mm
Length L	28.4 mm	Pin length P	17.4 mm
Pin width B	4.6 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------